

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Anti Roest Primer**
- **Article number:** 107
- **Unique formula identifier (UFI):** 0690-X0GR-U001-FN0T
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Anticorrosion additive

- **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**  
ChemTechniek Nederland BV  
Inductorstraat 8  
3903KB Veenendaal  
Nederland  
www.chemtechniek.nl  
info@chemtechniek.nl

- **1.4 Emergency telephone number:**

Nationaal Vergiftigingen Informatie Centrum (NVIC) : 088-755 8000  
(Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2                      H319                      Causes serious eye irritation.

STOT SE 3                      H336                      May cause drowsiness or dizziness.

Asp. Tox. 1                      H304                      May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412                      Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02    GHS07

- **Signal word** Danger

- **Hazard-determining components of labelling:**

acetone

xylene

Hydrocarbons C9-C11, n-alkanes, isoalkanes, cycloalkanes, &lt;2% aromatics

Hydrocarbons, C9, aromatics

- **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319                      Causes serious eye irritation.

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 48 (replaces version 47)

Revision: 03.03.2022

**Trade name: Anti Roest Primer**

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapours or spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P501 Dispose of contents / container in accordance with national regulations of the disposal.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards****Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336, EUH066	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	2.5-<5%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022


Version number 48 (replaces version 47)

Revision: 03.03.2022

**Trade name: Anti Roest Primer**

(Contd. of page 2)

 CAS: 7779-90-0  
 EINECS: 231-944-3

 trizinc bis(orthophosphate)  
 Aquatic Acute 1, H400; Aquatic Chronic 1, H410

0.1-&lt;1%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · After inhalation:

Supply fresh air; consult doctor in case of complaints.  
 Take affected persons into fresh air and keep quiet.

##### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.  
 Immediately remove any clothing soiled by the product.

##### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

##### · After swallowing:

Do not induce vomiting; call for medical help immediately.

#### · 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty  
 Headache  
 Dizziness  
 Dizziness  
 Nausea

#### · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.  
 Later observation for pneumonia and pulmonary oedema.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

##### · Suitable extinguishing agents:

Fire-extinguishing powder  
 Carbon dioxide  
 Use fire extinguishing methods suitable to surrounding conditions.  
 Foam

##### · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

##### · 5.3 Advice for firefighters

##### · Protective equipment:

Wear self-contained respiratory protective device.

##### · Additional information

Cool endangered receptacles with water spray.  
 Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.  
 Ensure adequate ventilation

Keep away from ignition sources.

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 48 (replaces version 47)

Revision: 03.03.2022

**Trade name: Anti Roest Primer**

(Contd. of page 3)

Ensure adequate ventilation.

**· 6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

**· 7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

**· Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

**· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:** Protect from heat and direct sunlight.**· 7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**· 8.2 Exposure controls****· Ingredients with limit values that require monitoring at the workplace:****CAS: 67-64-1 acetone**

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm
	Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm

**CAS: 106-97-8 butane, pure**

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

**CAS: 1330-20-7 xylene**

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 220 mg/m <sup>3</sup> , 50 ppm
	Sk, BMGV

**· DNELs****CAS: 67-64-1 acetone**

Oral	DNEL	62 mg(kg (ME)
Inhalative	DNEL	200 mg/m <sup>3</sup> (ME)

**· Ingredients with biological limit values:****CAS: 1330-20-7 xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

**· Additional information:** The lists valid during the making were used as basis.**· Appropriate engineering controls** No further data; see item 7.

(Contd. on page 5)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 48 (replaces version 47)

Revision: 03.03.2022

Trade name: Anti Roest Primer

(Contd. of page 5)

· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.82441 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Not determined.
· Explosive properties:	Not determined.
· Solvent separation test:	
· Organic solvents:	75.0 %
· VOC (EC)	618.3 g/l
· Solids content:	0.0 %
· Change in condition	
· Evaporation rate	Not applicable.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 48 (replaces version 47)

Revision: 03.03.2022

Trade name: Anti Roest Primer

(Contd. of page 6)

### SECTION 11: Toxicological information

#### · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### · Acute toxicity

##### · LD/LC50 values relevant for classification:

##### ATE (Acute Toxicity Estimates)

Dermal	LD50	23,557 mg/kg
Inhalative	LC50/4 h	>141 mg/l

##### CAS: 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	~76 mg/l (rat)

##### CAS: 74-98-6 propane

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

##### CAS: 106-97-8 butane, pure

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

##### Hydrocarbons C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Oral	LD50	8,000 mg/kg (rat)
Dermal	LD50	4,000 mg/kg (rat)
Inhalative	LC50/4 h	>18.5 mg/l (rat)

##### CAS: 75-28-5 isobutane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

##### CAS: 1330-20-7 xylene

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)

##### Hydrocarbons, C9, aromatics

Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rat)
Inhalative	LC50/4 h	>6,193 mg/l (rat)

##### CAS: 7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.7 mg/l (rat)

- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

##### · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 48 (replaces version 47)

Revision: 03.03.2022

Trade name: Anti Roest Primer



(Contd. of page 7)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN number or ID number</b></li> <li>· <b>ADR/RID/ADN, IMDG, IATA</b></li> </ul>   | UN1950   |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR/RID/ADN</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>  | UN1950 AEROSOLS<br>AEROSOLS<br>AEROSOLS, flammable |
| <ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR/RID/ADN</b></li> </ul> <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> | 2 5F Gases.<br>2.1                                 |
| <ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul> <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>  | 2.1 Gases.<br>2.1                                  |
| <ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR/RID/ADN, IMDG, IATA</b></li> </ul>  | Void   |
| <ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>   | No   |
| <ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> </ul>   | Warning: Gases.                                    |

(Contd. on page 9)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 48 (replaces version 47)

Revision: 03.03.2022

**Trade name: Anti Roest Primer**

(Contd. of page 8)

<ul style="list-style-type: none"> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Code</b></li>   <li>· <b>Segregation Code</b></li> </ul>	<p style="text-align: center;">-</p> <p>F-D,S-U</p> <p>SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.</p> <p>SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.</p>
<ul style="list-style-type: none"> <li>· <b>14.7 Maritime transport in bulk according to IMO instruments</b></li> </ul>	<p>Not applicable.</p>
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>ADR/RID/ADN</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li>   <li>· <b>Transport category</b></li> <li>· <b>Tunnel restriction code</b></li> </ul>	<p>1L</p> <p>Code: E0 Not permitted as Excepted Quantity</p> <p>2</p> <p>D</p>
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p>1L</p> <p>Code: E0 Not permitted as Excepted Quantity</p>
<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	<p>UN 1950 AEROSOLS, 2.1</p>

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.

(Contd. on page 10)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 03.03.2022

Version number 48 (replaces version 47)

Revision: 03.03.2022

**Trade name: Anti Roest Primer**

(Contd. of page 9)

H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous version altered.**